



FOAMING RELEASE AGENT forms a protective film on forms or surfaces exposed to concrete build-up. It will displace concrete and remain attached in spite of heavy abrasion, because of its ability to bond chemically to metal surfaces.

DIRECTIONS:

For mixers: Apply FOAMING RELEASE AGENT daily by brush swab or spray.

For pre-cast or pre-stress forms: Dilute 1 part of FOAMING RELEASE AGENT with 1 part Mineral Spirits and spray or wipe lightly on the metal forms.

For wood forms: Dilute 1 part FOAMING RELEASE AGENT with 1 part of fuel oil or diesel fuel and apply with a roller.

**FORMS A BOND RESISTANT
PROTECTIVE FILM ON SURFACES
EXPOSED TO CONCRETE BUILD-UP**

CAUTION – COMBUSTIBLE

Harmful or fatal if swallowed. Keep away from heat or open flame. See side panel for additional cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

**Western Environmental
Services, Inc.**

"It's not just our planet, it's our home!"

TO ORDER CALL TOLL FREE 1-800-574-3948

Visit us today at www.western-environmental.com

CAUTION – COMBUSTIBLE

Harmful or fatal if swallowed. Keep away from heat or open flame. Contains petroleum distillates. Avoid contact with skin, eyes or clothing. Use only with adequate ventilation.

FIRST AID

External – Wash with soap and water.

Internal – Do NOT induce vomiting. Call physician immediately.

Eyes – Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

KEEP OUT OF REACH OF CHILDREN

38580609

NET CONTENTS:

5 6 20 30 35 55
GALLONS