



This synthetic metalworking coolant and lubricant is designed for use on all ferrous and non-ferrous metals – contains no silicone or sulfur. It uses special corrosion inhibitors to help protect finished work from flash rusting. When diluted for use, it makes a clear solution to give the operator an unobstructed view of the workpiece. Dilution ratios can be varied to meet severe or mild conditions.

DIRECTIONS

Reservoirs should be drained and flushed free of all old lubricant. For severe operations and hard metals, use a 10:1 dilution. Light duty operations may use a dilution of 20:1 or 30:1.

For best results, monitor the tool temperature to determine proper dilution for a particular operation.

**FOR CUTTING, GRINDING,
DRILLING AND TAPPING**

BIODEGRADABLE

CAUTION

Harmful if swallowed. See side panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

***Western Environmental
Services, Inc.***

***“It’s not just our planet, it’s our home!”
TO ORDER CALL TOLL FREE 1-800-574-3948
Visit us today at www.western-environmental.com***

CAUTION

Harmful if swallowed. Avoid contact with eyes, skin or mucous membranes. In case of contact, flush with plenty of water for at least 15 minutes and obtain medical attention. If irritation persists, obtain medical attention. If swallowed, give several glasses of water and induce vomiting. Call a physician immediately.

KEEP OUT OF REACH OF CHILDREN

30382008

NET CONTENTS:

5 6 20 30 55

GALLONS