



SPRAY SILICONE

**MEDIUM VISCOSITY • LIGHT DUTY
NO GUMMING • REDUCES FRICTION
PROTECTS AND RENEWS**

NET WEIGHT: 13 oz. (369 g.)

DANGER: EXTREMELY FLAMMABLE

VAPOR HARMFUL

Harmful or Fatal if swallowed.

Contents under pressure.

See additional cautions on side panels.

KEEP OUT OF REACH OF CHILDREN

Sold By:

Western Environmental Services, Inc.

"It's not just our planet, it's our home!"
TO ORDER CALL TOLL FREE 1-800-574-3948
 Visit us today at www.western-environmental.com

DESCRIPTION

SILI-SLIDE is a general purpose silicone lubricant formulated to stop sticking, binding and squeaking. It is a unique formulation of a reacted-grade silicone and fast-evaporating solvents, with fine-mist spray pattern that allows for even and controlled silicone distribution. When used as directed does not cause "fish eyes" in paint, and is therefore useful in auto-body shops, mold-release, and other applications where paintability is required. **SILI-SLIDE** is also excellent for metal-to-metal, aluminum, rubber & plastic lubrication, thread & fiber lubes, and rubber & plastic mold release applications.

APPLICATIONS

Automotive Industry - Prevents freezing of lock mechanisms, lubricates rubber door and window seals, lubricates and protects parts.
Packaging & Processing Industry - Lubricates movable parts on all packaging and processing machinery. Helps reduce rusting of exposed metal.
Textile Industry - Reduces friction on ironing and pressing equipment. Use on cutting tables to prevent binding and provide smooth and even cutting.
Mold Release - Excellent for rubber, plastic & paintable mold release applications.
SILI-SLIDE can also be used on Vending Equipment, Molding Equipment, Dry Cleaning Equipment and other applications where lubrication is required.

DIRECTIONS

Thoroughly clean surface to be sprayed. Hold can 8 to 10" from surface. Spray lightly with a sweeping motion. Avoid over-spraying. On sticking parts, work back and forth to allow good penetration. Wipe off excess with a clean cloth.

DANGER: EXTREMELY FLAMMABLE

Use only with adequate ventilation. Keep out of reach of children. Avoid excessive inhalation of fumes and repeated or prolonged contact with skin. Contents under pressure. Do not expose to heat or store at temperatures exceeding 120°F. Do not puncture or incinerate container. Wrap empty container and put in trash collection.

FIRST AID:

If Swallowed: Do not induce vomiting. Get medical attention immediately.
If Inhaled: Move to fresh air. If breathing has stopped, administer artificial respiration. Get medical attention.

If On Skin: Thoroughly wash with soap and water. Get medical attention if irritation persists.

If In Eyes: Flush with liberal amounts of water, lifting eyelids occasionally. Consult physician.

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold as is and the manufacturer makes no warranty, express or implied, of merchantability, fitness for a particular purpose or otherwise.

HMIS Ratings	
Flammability	4
Health	2
Reactivity	0
Personal Protection	G

Chemical Name	C.A.S. Number
Hexane	110-54-3
Propane	74-98-6
Butane	106-97-8
Silicone Fluid	.68952-01-2