

MATERIAL SAFETY DATA SHEET

Western Environmental Services, Inc.
P.O. Box 9035
Scottsdale, AZ 85252

GENERAL INFORMATION NUMBER: (602) 234-8873

REVISION DATE: August 1, 2002
DATE OF ISSUE: March 23, 2004

I - Product Identification

Super Tile

PRODUCT CODE: 0144

CHEMICAL FORMULATION: Acid based cleaning solution.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 2

FLAMMABILITY: 1

REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Glycolic acid	1.00-5.00	N/E	N/E	N	N	N	79-14-1
Isopropanol	1.00-5.00	400 ppm	400 ppm	N	N	N	67-63-0
Sulfamic acid	1.00-5.00	100 ppm	100 ppm	N	N	N	5329-14-6

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D

SPECIFIC GRAVITY (WATER = 1): 1.02

VAPOR PRESSURE (mm Hg): N/D

VOC CONTENT (% by weight): 1.00-10.0

VAPOR DENSITY (AIR = 1): N/D

EVAPORATION RATE (WATER = 1): ~ 1.0

SOLUBILITY IN WATER: Soluble

pH: 1.0

APPEARANCE AND ODOR: Hazy, blue liquid; floral fragrance.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): > 200

(TEST METHOD): Closed cup

FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/A LOWER: N/A

EXTINGUISHING MEDIA: Water, foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: None.

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong alkalis.

CONDITIONS TO AVOID: None.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY **INHALATION:** X **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X

INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None.

EFFECTS OF OVEREXPOSURE

IF IN EYES: Severe irritation, redness, tearing, blurred vision. May cause destruction of tissue, depending upon length of exposure.

IF ON SKIN: Redness and irritation, with prolonged or repeated exposure.

IF SWALLOWED: Burns to mucous membranes, gastrointestinal irritation, cramps.

IF INHALED: Irritation to upper respiratory tract.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Remove contaminated clothing and launder before reuse. Flush with water water. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Give affected person 1 to 2 glasses of water followed by milk of magnesia or vegetable oil. Do not induce vomiting. Never give anything to an unconscious person.

IF INHALED: Remove person to fresh air. If irritation persists, obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area and contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal or flush away with water.

WASTE DISPOSAL METHOD: Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION

LOCAL: Recommended

MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses or chemical goggles

OTHER PROTECTIVE EQUIPMENT: Protective clothing

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: Compounds, cleaning liquid (sulfamic acid)

DOT CLASS: 8

DOT ID NUMBER: UN1760

DOT PACKING GROUP: III

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: August 1, 2002

Prepared by: PMR

DATE OF ISSUE: March 23, 2004

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Western Environmental Services, Inc. assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.